

### CHARACTERISTICS

Finish: Natural Utilization groups: 4 - For high traffic Boxes / Pallet: 24 Rectified sides Kg / Box: 41.69 Kg / Pallet: 1000.6 Degree of detonation: V3 (Medium) Material: Glazed porcelain tiles Pieces / Box: 7 M2 / Box: 2.52 M2 / Pallet: 60.48



Installation Installation: Coating



mm



Installation Installation: Pavement



Critical angle of slip (DIN 51130 -Ramp) Critical sliding angle (DIN 51130 - Ramp): R-10



Critical angle of slip in wet areas when walking barefoot (DIN 51097 -Ramp)

Critical angle of slip in wet areas when walking barefoot (DIN 51097 - Ramp):



Slip resistance (CTE ENV 12633 -Pendulum) Slip resistance (CTE ENV 12633 -Pendulum): Clase 1

### LIMESTONE

## Limestone Blanco 60X60R

PRICE / M2 (VAT INCLUDED)



#### Glazed Porcelain

Suitable for all types of floor and wall applications, interior, exterior, facades as well as bathrooms and kitchens.



Recycling Recycled:

# Limestone

Essential neutrality. Shades and a mix of reflections bring life and realism to a collection inspired by limestone compounds to carefully replicate every particle, luminescence or nuance of these surfaces. Limestone is a classical and timeless proposal aimed at simple and essential interiors. Neutral places away from any noise, spaces at the service of an objective, giving all the protagonism to those who live in them, to their wishes and goals, always within grasp. In modular formats, whether rectified or not, its decorated lines, Ocala and Bosco, replicate the finish in wooden planks, thus allowing different combinations.



### MANUALS AND RESOURCES

Product technical certificate

#technology\_text

## **Glazed** Porcelain

## **Glazed Porcelain**

Suitable for all types of floor and wall applications, interior, exterior, facades as well as bathrooms and kitchens.